



INSTRUCTIONS :

- 1.TACK WELDS CAN BE MADE IN ANY POSITION WITH ANY PROCESS IN THE MOST LOGICAL SEQUENCE FOR STRUCTURAL SQUARENESS AND JOINT ACCESS.
- 2.ALL TACK WELDS ARE TO BE MADE SHORTER THAN 15 mm AND PLACED ON THE OUTSIDE OF THE VESSEL ONLY.
- 3.ALL WELDS ARE TO BE MADE AS INDICATED ON DRAWING.
- 4.ALL FILLET WELDS EXCEPT SPECIAL NOTES ARE TO BE 10 mm (+2mm/-0mm) IN LEG LENGTH.
- 5.COMPLETE ALL WELDING WITH BASE "A" IN THE FLAT POSITION.
- 6.GRINDING WILL BE LIMITED TO : TACK WELDS , STARTS , STOPS , ROOT PASS , FACE AND TOES.
- 7.POST CLEANING : WIRE BRUSH ONLY AFTER SLAG REMOVAL , NO GRINDING.

NOTE: ALL DIMENSTIONS IN MILLIMETRE

Test Project for the 45th WorldSkills Competition in Kazan, Russia 2019.
Copyright © 2019 WorldSkills International.
All Rights Reserved.

Skill: 10. Сварочные технологии, Welding, Schweißen, Soudage				OR	
Scale: N. T. S	Date: 18. Aug. 2019	Paper: A3			
Drawn/Designed by: Chih-Peng Chen TW			Drawing No:WSC2019_TP10_TW_PV_SYMBOLS_ISO E		
Description: Pressure Vessel-SYMBOLS			Rev: 04	Page:	
			Appd:	Sign:	